

-EXHIBIT A-

EXTERIOR PLASTER - HARD COAT EXTERIOR STUCCO FINISH (Section 2512):

Completion Date: _____

THE EXTERIOR INSTALLATION FINISH HARD COAT STUCCO SYSTEM UNDER SECTION 2512 & TABLE 2512.6 OF THE INTERNATIONAL BUILDING CODE (IBC):

CONFORMS _____

Address of Structure:

Describe Area of Work:

INSTALLATION

CONFORMS

- | | |
|---|-------|
| 1) Metal lath/wire fabric & connectors | _____ |
| 2) Weep screeds | _____ |
| 3) Application of coats per Table 2512.6* | _____ |
| 4) Curing and intervals per Table 2512.6* | _____ |

*Plastering with cement plaster shall be not less than three coats when applied over metal lath or wire fabric lath or gypsum board backing as specified in Section 2510.5 IBC and shall be not less than two coats when applied over masonry or concrete.

If the plaster surface is to be completely covered by veneer or other facing material, or is completely concealed by another wall, plaster application need only be two coats, provide total thickness is as set forth in ASTM C 926.

The information listed is certification that the installation conforms to **Section 2512, EXTERIOR PLASTER of the International Building Code (IBC.)**

Contractor/Installer Company Name(s) and Address:

Signature: _____
Print Name & Title: _____
Telephone Number: _____

